





# NETLIFT®

- 1.5 - 3.5 Ton LPG Forklift  
1.5 - 3.5 Ton LPG Forklift Trucks




LPG Forkliftler - M SERİSİ  
LPG FORKLIFT TRUCKS - M SERIES

### Motor Seçenekleri

#### OPTIONS OF ENGINE



#### GCT



**Tip/ Type:** WA3  
**Model:** K25  
**Çıkış gücü/ Rated output:** 37.4 kw/ 2300rpm  
**Tork/ Rated torque:** 171.2 N.m/ 1600rpm  
**Silindir sayısı/ No. of cylinder:** 4  
**PistonxStrok/ BorexStroke:** 89 x 100 mm  
**Deplasman/ Displacement:** 2.488L

### 1.5t - 1.8t - 2t - 2.5t - 3t - 3.5t LPG Forklift Teknik Özellikleri / 1.5t-1.8t-2t-2.5t-3t-3.5t LPG Forklift Tech. Specifications

Genel/ General		Model / Basic Model	NGL15T-M2	NGL18T-M2	NGL20T-M2	NGL25T-M2	NGL30T-M2	NGL35T-M2			
Tip/ Type		WB3	WB3	WA3 / GB3	WA3 / GB3	WA3 / GB3	WA3 / GB3	WA3 / GB3			
Güç tipi/ Power type		Gasoline/LPG	Gasoline/LPG	Gasoline/LPG	Gasoline/LPG	Gasoline/LPG	Gasoline/LPG	Gasoline/LPG			
Kapasite/ Rated capacity		kg	1500	1800	2000	2500	3000	3500			
Yük merkezli/ Load centre		mm	500	500	500	500	500	500			
Kaldırma yüksekliği/ Lift height		mm	3000	3000	3000	3000	3000	3000			
Serbest kaldırma yüksekliği/ Free lift height		mm	135	135	150	150	165	170			
Çatal ölçüsü/ Fork size		L x W x T	920x100x35	920x100x35	1070x122x40	1070x122x40	1070x125x45	1070x130x50			
Çatal ayar aralığı/ Fork regulating range		Min./ Max	200/890	200/890	250 / 1040	250 / 1040	250 / 1100	260 / 1100			
Asansör tilt açısı/ Mast tilt angle		F/R	° 6°/12°	° 6°/12°	° 6°/12°	° 6°/12°	° 6°/12°	° 6°/12°			
Ön çıkıntı/ Front overhang		mm	400	400	465	465	485	505			
Arka çıkıntı/ Rear overhang		mm	465	510	465	495	520	585			
Min.zemin açıklığı(Asansör altı)/ Min.ground clearance(Bottom of mast)		mm	130	130	125	125	140	140			
Toplam ölçüler/ Overall dimensions		Gövde uzunluğu (çatalsız)/ Length to face of fork(without fork)	mm	2255	2300	2510	2545	2685	2750		
		Genişlik/ Overall width	mm	1070	1070	1150	1150	1210	1210		
		Asansör kapalı yükseklik/ Mast lowered height	mm	2015	2015	2010	2010	2075	2150		
		Asansör açık yükseklik (braketli)/ Mast extended height (with backrest)	mm	3984	3984	3990	3990	4100	4160		
Kabin yüksekliği/ Overhead guard height		mm	2110	2110	2145	2145	2170	2170			
Dönme yarıçapı(dış)/ Turning radius (outside)		mm	2040	2075	2180	2250	2430	2450			
Koridor istifleme genişliği/ Min right angle stacking aisle width (add load length and clearance)		mm	1825	1857	1940	2010	2140	2160			
Performans/ Performance		Hız/ Speed	Sürüş (yüksüz)/ Travel (Unladen)	km/saat(h)	14.5	14.5	19(WA3)20(GB3)	19(WA3)20(GB3)	19		
			Kaldırma (yükülü)/ Lifting (Laden)	mm/sn(sec)	380	380	520	520	420	330	
			İndirme (yükülü)/ Lowering (Laden)	mm/sn(sec)	450	450	450	450	450	450	
		Max. çekiş gücü (yükülü/ yüksüz)/ Max.Drawbar pull (Laden/unladen)	KN	17/15	17/15	17/15	17/15	17/15	17/15		
Max. turmanma (yükülü)/ Max. Gradeability (Laden)		%	20	20	20	20	20	18			
Şase/ Chassis		Lastik/ Tyre	Ön/ Front	6.50-10-10PR	6.50-10-10PR	7.00-12-12PR	7.00-12-12PR	28x9-15-14PR	28x9-15-14PR		
			Arka/ Rear	5.00-8-8 PR	5.00-8-8 PR	6.00-9-10 PR	6.00-9-10 PR	6.50-10-10 PR	6.50-10-10 PR		
		Lastik iz genişliği/ Tread	Ön/ Front	mm	890	890	970	970	1000	1000	
			Arka/ Rear	mm	920	920	980	980	980	980	
Dingil mesafesi/ Wheelbase		mm	1400	1400	1600	1600	1700	1700			
Yakıt tankı kapasitesi/ Fuel tank capacity		L	50	50	60	60	70	70			
Ağırlık/ Weight		Serbest ağırlık/ Self weight		kg	2590	2800	3450	3620	4310	4750	
		Yük dağılımı/ Weight distribution	Yükü/ Laden	Ön aks/ Front Axle	kg	3520	3950	4690	5260	6290	7090
				Arka aks/ Rear Axle	kg	570	650	760	860	1020	1160
			Yüksüz/ Unladen	Ön aks/ Front Axle	kg	1180	1260	1550	1630	1940	2140
Arka aks/ Rear Axle	kg			1430	1540	1900	1990	2370	2610		
Akü/ Battery		Voltaj-Kapasite/ Voltage-Capacity		V/Ah	12/ 60	12/ 60	12/ 60	12/ 60	12/ 60		
Şanzıman/ Transmission		Tip/ Type			Powershit	Powershit	Powershit	Powershit	Powershit		
		Kademe/ Stage	F/R			1/1	1/1	1/1	1/1	1/1	
			Çalışma basıncı ataşmanlar için/ Operating pressure (For attachments)		MPa	14,5	14,5	17,5	17,5	17,5	17,5

